



PILOT Commercial Series

A New Dimension in Stereolithography 3D Printing

- Lower operation & maintenance costs with excellent stability throughout entire life cycle.
- Tailored for exquisite parts with open design for materials and machine access.
- Printed parts demonstrate excellent sidewall quality and fine detail.

System Features

- Scanning speed can reach 12-15 m/s.
- Automatically controlled the surface level and processing parameters.
- Marble recoating substrate can realize 0.05mm layer thickness stably to get excellent surface quality.
- CE certification.
- Convenient to assembly and disassembly platform.
- Replaceable resin tank.
- Automatic odor removal, office environment.

Versatile Application Range · High Accuracy · Excellent Surface Aesthetics



Technical Data

* Specifications are subject to change;
consult with your sales representative for confirmation of current offering.

	PILOT 250	PILOT 450
Build Envelope Capacity	9.8 x 9.8 x 9.8 in (250 x 250 x 250 mm)	17.7 x 17.7 x 15.7 in (450 x 450 x 400 mm)
Maximum Part Weight	38.6 lb (17.5 kg)	77.2 lb (35 kg)
Accuracy	Part size < 1 in (25.4 mm): ±0.001 in (±0.025 mm) Part size ≥ 1 in (25.4 mm): ±0.1% x L	Part size < 3.9 in (100 mm): ±0.004 in (±0.1 mm) Part size ≥ 3.9 in (100 mm): ±0.1% x L
Beam Size	Standard Beam (0.12 – 0.20 mm) or Small Beam (0.06 – 0.08 mm) ,optional	Nominal 0.003 -0.005 in (0.08 -0.12 mm)
Scanning Speed	12m/s (Maximum); 6 -10m/s	15m/s (Maximum); 6-10m/s (Typical)
Layer Thickness	0.002 in (0.05 mm) minimum; 0.01 in (0.25 mm) maximum	0.002 in (0.05 mm) minimum; 0.01 in (0.25 mm) maximum
Weight	1709 lb (775 kg) (with 106 lb (48 kg) initial fill inside)	2392 lb (1085 kg) (with 353 lb (160 kg) initial fill inside)
Machine Size (WxDxH)	43.5 x 41.4 x 77.3 in (1105x1052x1965 mm)	52.4 x 53.9 x 84.3 in (1331x1368x2140 mm)
Scanning Mode	2D	2D

PILOT 250 / 450

Laser	Solid-state frequency tripled Nd: YVO ₄
Wavelength	354.7 nm
Controller	UnionTech™ RSCON
Part Preparation	Materialise Magics
Operating Systems	Windows 7, Windows 10
Input Data File Format	STL
Network Type and Protocol	Ethernet, IEEE 802.3 using TCP/IP and NFS
Electrical Requirements	200-240 VAC,50/60 Hz,single phase
Laser Warranty	5,000 hours or 15 months (whichever comes first)
Base Plate/Recoater Rim	Granite
Systems Control	Closed-loop
Power (nominal)	Typically 250 ~350mW (@100kHz) on the target surface of the material under nominal optical path condition

Operating Environment:

Temperature Range	72–79°F (22–26°C)
Maximum Change Rate	1 °C/hour
Relative Humidity	< 40 % non-condensing

Accessories :

Additional Resin Vat	Optional for PILOT 250
Platform Change Carts	Manual offload cart optional for PILOT 450
Processing and Finishing	Post-Curing Unit
System Warranty	One-year warranty (under UnionTech's Purchase Terms and Conditions)

UnionTech

Shanghai Union Technology Corporation
Room 102, Unit 40, 258 Xinzhuan Rd, Shanghai, 201612, China
enquiry@uniontech3d.cn
www.uniontech3d.com

Union Tech, Inc.
100 Illinois St., Suite 200, St. Charles, Illinois, 60177, USA
info@uniontech3d.com

UnionTech GmbH
Friedrich-Ebert Anlage 36, Frankfurt, Hessen, 60325, Germany
info@uniontech3d.com