

# SAFETY DATA SHEET

1. Identification

Important information \*\*\* This Safety Data Sheet is only authorised for use by HP for HP Original products. Any

unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action

being taken by HP. \*\*\*

Product identifier V1R12Series

Other means of identification None.

**Recommended use** Materials to be processed in HP 3D MJF equipment only.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

HP Inc.

1501 Page Mill Road Palo Alto, CA 94304-1112

**United States** 

**Telephone** 650-857-1501

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048

**HP Inc. Customer Care** 

Line

(Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

# 2. Hazard(s) identification

Physical hazardsNot classified.Health hazardsNot classified.Environmental hazardsNot classified.OSHA defined hazardsNot classified.

Label elements

Hazard symbol None.

Signal word Warning

**Hazard statement** May form combustible dust concentrations in air.

**Precautionary statement** 

Prevention Take precautionary measures against static discharge. Use with adequate ventilation. Avoid

generation or accumulation of dust.

Response If inhaled, remove to fresh air. Get medical attention if symptoms persist. IN CASE OF FIRE, use

water spray or fog, foam, dry chemical or CO2. Collect in a chemical waste container. Use only

vacuum cleaners approved for combustible dust collection.

Storage Not available.

Disposal Not available.

Hazard(s) not otherwise

May form combustible dust concentrations in air.

classified (HNOC) Risk of skin burns caused by hot melt.

GHS Supplemental information This material is considered hazardous under the OSHA Hazard Communication Standard criteria,

based on hazard(s) not otherwise classified.

### 3. Composition/information on ingredients

**Mixtures** 

Material name: V1R12Series sps us

14387 Version #: 10 Revision date: 06-Nov-2019 Issue date: 30-Oct-2017

% Chemical name Common name and synonyms **CAS** number >= 98% Proprietary polymer Proprietary This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard Composition comments Communication Standard). 4. First-aid measures Inhalation If dust from the material is inhaled, remove the affected person immediately to fresh air. Move to fresh air in case of accidental inhalation of vapors or decomposition products. If breathing is difficult, give oxygen. Oxygen or artificial respiration if needed. Consult a physician for specific advice. Wash the skin immediately with soap and water. In case of contact with molten product, cool Skin contact rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily. Dust: Wash well-open eyes immediately, abundantly and thoroughly with water. Remove particle Eve contact remaining under the eyelids. If irritation persists, consult a doctor. On contact with hot product: Cool eyes rapidly with cold water after contact with molten polymer. Continue to rinse for at least 15 minutes. Get medical attention immediately. If swallowed, do NOT induce vomiting. Get medical attention. Never give anything by mouth to an Ingestion unconscious person. Most important No experiences of acute or chronic damages in humans have been made yet. symptoms/effects, acute and delayed **General information** Risk of skin burn caused by hot melt. Do not leave the victim unattended. Remove victim immediately from source of exposure.

# 5. Fire-fighting measures

Suitable extinguishing media
Unsuitable extinguishing

Water spray, foam, dry powder or carbon dioxide.

Do not use water jet as an extinguisher, as this will spread the fire.

Victim to lie down in the recovery position, cover and keep him warm.

media
Specific hazards arising from the chemical

May be released in case of fire: carbon monoxide, carbon dioxide, nitric oxides, organic products of decomposition. Under certain fire conditions, traces of other toxic products may occur.

Special protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions
General fire hazards

Do not use a solid stream of water. A solid stream of water can cause a dust explosion. Fire fighting equipment should be thoroughly decontaminated after use.

Dust clouds generated during handling and/or storage can form explosive mixtures with air. Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

In case product dust is released: Dust mask

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable container for disposal. If a vacuum is used, the motor must be rated as dust explosion-proof. Dispose of in compliance with federal, state, and local regulations.

**Environmental precautions** 

Prevent further leakage or spillage. Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

# 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes Avoid breathing dust. Prevent dust accumulation to minimize explosion hazard. Inside and outside the equipment should be cleaned regularly with an explosion-protected vacuum cleaner to avoid dust accumulation. Do not sweep the dust or or try to remove it with a compressed-air gun. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Conditions for safe storage, including any incompatibilities

Store away from moisture and heat to maintain the technical properties of the product. Eliminate sources of ignition. Do not expose to heat or store above 60 C.

# 8. Exposure controls/personal protection

# Occupational exposure limits

Also see Exposure guidelines.

**ACGIH** 

 Material
 Type
 Value

 V1R12Series
 TWA
 3 mg/m3

Comments: Respirable particles

10 mg/m3

Comments: Inhalable Particles

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Particles Not Otherwise Specified / Nuisance Dust

US OSHA (PEL:Z-1): 5 mg/m3 Respirable fraction

US OSHA (PEL:Z-1): 15 mg/m3 Total dust

US OSHA (TWA:Z-3): 15millions of particles per cubic foot of air Respirable fraction

US OSHA (TWA:Z-3): 50millions of particles per cubic foot of air Total dust

US OSHA (TWA:Z-3): 5 mg/m3 Respirable fraction

US OSHA (TWA:Z-3): 15 mg/m3 Total dust

# Appropriate engineering controls

HP recommends the use of HP accessories for unpacking 3D parts and refilling the build chamber. If other methods are used, read the following: Dust clouds generated during handling and/or storage can form explosive mixtures with air. Dust explosion characteristics vary with the particle size, particle shape, moisture content, contaminants, and other variables. Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to fall freely or be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Consult ACGIH ventilation manual, NFPA Standard 91 and NFPA Standard 654 for design of exhaust system and safe handling.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields.

Skin protection

**Hand protection** Wear impermeable gloves. Protective heat-insulating gloves are to be used during thermal

processing. Any areas of skin covered with dust must be washed immediately with soap and water

as the powder draws out natural moisture from the skin. Use barrier cream regularly.

Other Processing of this product releases vapors or fumes which may cause skin irritation. It is a good

industrial hygiene practice to minimize skin contact. Wash thoroughly after handling.

**Respiratory protection**Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded, use NIOSH approved respiratory protection

equipment appropriate to the material and/or its components and substances released during

processing.

Thermal hazards In thermal processing: Risk of skin burns. Wear appropriate thermal protective clothing, when

necessary.

# 9. Physical and chemical properties

Appearance Powder. Solid.

Physical state Not available.
Form Powder.

Color Transparent, translucent.

Material name: V1R12Series

14387 Version #: 10 Revision date: 06-Nov-2019 Issue date: 30-Oct-2017

Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point 392 - 396 °F (200 - 202.22 °C)

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

**Decomposition temperature**  $> 662 \, ^{\circ}\text{F} \ (> 350 \, ^{\circ}\text{C})$ 

Viscosity Not available.

Other information

**Explosive properties** Dusts might form explosive mixtures with air.

Powder explosivity data:

Minimum Ignition Energy (MIE) "dust cloud" w/ Inductance >30mJ. Layer Ignition Temperature (LIT) "dust layer" >400degC. Minimum Ignition Temperature (MIT) "dust cloud" >360degC.

Auto Ignition Temperature (AIT) 442degC.

Oxidizing properties Not oxidizing.

# 10. Stability and reactivity

**Reactivity** Under normal conditions: stable.

**Chemical stability** The product is stable under normal handling and storage conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Take measures to mitigate material spillage and avoid potential ignition sources such as ESD

(ElectroStatic Discharges), flames, and sparks. Do not smoke nearby. Avoid wet/humid

environment. Recommended working humidity 50-70%. Avoid dust formation.

Incompatible materials Oxidizing materials, acids, strong bases, water and high humidity.

Hazardous decomposition

products

Thermal decomposition: Decomposition temperature: > 350 °C 300 - 350 °C: possible formation of:, Monomer and oligomer (white fumes) Temperature exceeding 350°C:, Thermal decomposition giving toxic and corrosive products:, Carbon monoxide, Ammonia, Amino derivatives Temperature exceeding 500 °C:, Formation of toxic products through combustion:, Carbon oxides, Hydrogen

# cyanide (hydrocyanic acid), (traces).

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation** At high temperature, products of thermal decomposition can be irritating to respiratory system.

Skin contact May be considered as comparable to a similar product for which experimental results are: Non

irritating to skin.

Eye contact May be considered as comparable to a similar product for which experimental results are: Not

irritating to the eyes.

Ingestion May be considered as comparable to a similar product for which experimental results are: Slightly

harmful by ingestion.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

### Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye

Based on available data, the classification criteria are not met.

irritation

Respiratory or skin sensitization

Respiratory sensitization
Skin sensitization
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Carcinogenicity
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**Based on available data, the classification criteria are not met. **Specific target organ toxicity -**Based on available data, the classification criteria are not met.

single exposure

Considir toward aware towisi

Specific target organ toxicity - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Further information Complete toxicity data are not available for this specific formulation

# 12. Ecological information

**Ecotoxicity** No ecotoxicity data noted for the ingredient(s).

Persistence and degradability

Bioaccumulative potential

Mobility in soil

Other adverse effects

Not available.

Not available.

Not available.

# 13. Disposal considerations

**Disposal instructions** Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

Further information Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

Material name: V1R12Series SDS US

### 15. Regulatory information

US federal regulations US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA

All ingredients are listed or exempt.

US TSCA 12(b): Does not contain listed chemicals.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations Not Listed

under chemical substances notification laws in the following countries: US (TSCA), EU

(EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

### 16. Other information, including date of preparation or last revision

Issue date30-Oct-2017Revision date06-Nov-2019

Version # 10

Other information This SDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

**Disclaimer** This Safety Data Sheet document is provided without charge to customers of HP. Data is the most

current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other

countries.

# **Explanation of abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

**DOT** Department of Transportation

**EPCRA** Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

**REC** Recommended

**REL** Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

**TLV** Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds